Box Turning Basics: References

For a ZVW Presentation on August 26, 2010, by Irv Miller

ZVW Library References

Turned Boxes - A 3 DVD Set Ray Key

DVD 1: The Basic Box
DVD 2: The Capsule Box
DVD 3: The Finial Box

Turning Boxers and Other Bonnie Klein Volume III of a 3 volume set

Projects of DVDs

Turn It Up - A 3 DVD Set Jimmy Clewes DVD 2: Lidded box from Box

Elder with a chattered Ebony

insert.

Turning Wood Richard Raffan Video Tape including details

of end grain turning and a

domed box project.

Taunton's Complete Illustrated Guide to Turning

Richard Raffan

Pages 146 to 145: End-Grain Hollowing and Shaping

Pages 167-169: *Box*

Internet References

http://www.woodturningonline.com/Turning/Projects/boxes.html

http://www.woodturningonline.com/Turning/Turning content/Turning End Grain Box.pdf

Notes on Hollowing

Jimmy Clews uses a parting tool as a scraper, a blunt angled bowl gouge (preferably from outside toward the center), and a straight chisel (90 degree skew) as a scraper for hollowing.

Bonnie Klein uses a fingernail grind spindle gouge, sometimes from the outside toward the center, sometimes from the center outward, and scrapers for hollowing. She also uses a blunt angle spindle gouge and no scraper for her acorn box hollowing.

Richard Raffan uses a blunt angle spindle gouge and scrapers, or scrapers only, for hollowing after drilling a depth hole.

Ray Key uses a blunt angled spindle gouge that he first uses as an auger to drill a hole in the center, then uses as a gouge to hollow from the hole outward. He finishes hollowing with a scraper.

Box Turning Basics: Order

For a ZVW Presentation on August 26, 2010, by Irv Miller

- 1. Rough turn a blank to a cylinder.
- 2. Turn tenons=spigots on each end for chucking.
- 3. Part off the lid from the base.
- 4. Chuck the lid
- 5. Touch up the lid cylinder and square off the end with a very slight undercut.
- 6. Hollow the lid, making sure that the flange that will contact the base is parallel with the lathe axis.
- 7. Sand and finish the inside of the lid to completion.
- 8. Remove the lid from the chuck
- 9. Chuck the base.
- 10. Touch up the base and square off the end.
- 11. Turn the tenon on the base for the lid, fitting the lid to a tight fit.
- 12. Hollow the base, making sure that the inside of the rim is parallel with the lathe axis. This is necessary for reverse chucking in a jam chuck.
- 13. Sand and finish the inside of the base to completion.
- 14.Place the lid on the base and turn the box to the desired style.
- 15. Start a parting cut for the bottom of the base.
- 16.Sand and finish the box, with the exception of the box bottom, to completion.
- 17. Fine tune the lid fit.
- 18. Remove the lid.
- 19.Part off the base.
- 20. Reverse chuck the base in a jam chuck.
- 21. Turn the base with a concave surface.
- 22.Sand and finish the base.